

Current transformer - PACT MCR-V2-6315- 95-1250-5A-1 - 2277239

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Window-type current transformer, 1,250 A AC primary current; 5 A AC secondary current; accuracy class 1; 10 VA rated power

Product Features

- Primary rated current I_{pn}: 0 ... (200 ... 2500) A
- Circular conductor dimensions: Ø 53 mm
- Rail dimensions: 63 x 15 mm, 2x 50 x 10 mm, 40 x 40 mm



Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 520.0 GRM |
| Custom tariff number | 85043129 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|------------------------------------|--------|
| Primary round conductor (diameter) | 53 mm |
| Primary round conductor (width) | 63 mm |
| Primary round conductor (height) | 15 mm |
| Note on dimensions | 2 |
| Primary round conductor (width) | 50 mm |
| Primary round conductor (height) | 10 mm |
| Width | 30 mm |
| Height | 121 mm |
| Depth | 95 mm |
| Width with alternative assembly | 95 mm |
| Height with alternative assembly | 121 mm |

Current transformer - PACT MCR-V2-6315- 95-1250-5A-1 - 2277239

Technical data

Dimensions

| | |
|---------------------------------|-------|
| Depth with alternative assembly | 30 mm |
|---------------------------------|-------|

Ambient conditions

| | |
|---|------------------|
| Ambient temperature (operation) | -25 °C ... 40 °C |
| Ambient temperature (storage/transport) | -25 °C ... 40 °C |

Input data

| | |
|-------------------------------------|--------------------------|
| Thermal rated short-time current | $I_{th} = 60 * I_n$ |
| Rated surge current | $I_{dyn} = 2.5 * I_{th}$ |
| Rated frequency: Standard converter | 50 Hz ... 60 Hz |
| Surge current limitation factor | FS 5 |
| Rated power | 10 VA |
| Primary rated current I_{pn} | 0 A ... 1250 A |
| Secondary rated current I_{sn} | 5 A AC |

General

| | |
|---------------------------|------------------------------------|
| Converter type | Plug-on converters |
| Class | 1 |
| Can be calibrated | no |
| Rated insulation voltage | 1 kV |
| Test voltage input/output | 3 kV (50 Hz, 1 min.) |
| Standards/regulations | IEC 60044-1 |
| Color | black |
| Housing material | Polyamide PA fiberglass reinforced |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27210902 |
| eCl@ss 4.1 | 27210902 |
| eCl@ss 5.0 | 27210902 |
| eCl@ss 5.1 | 27210902 |
| eCl@ss 6.0 | 27210902 |
| eCl@ss 7.0 | 27210902 |
| eCl@ss 8.0 | 27210902 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001505 |
| ETIM 3.0 | EC001505 |

Current transformer - PACT MCR-V2-6315- 95-1250-5A-1 - 2277239

Classifications

ETIM

| | |
|----------|----------|
| ETIM 4.0 | EC002048 |
| ETIM 5.0 | EC002048 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 30211501 |
| UNSPSC 7.0901 | 39121019 |
| UNSPSC 11 | 39121006 |
| UNSPSC 12.01 | 39121006 |
| UNSPSC 13.2 | 39121006 |

Drawings

Dimensioned drawing

