

## Specification Sheet

Part Number: 170-03030



Braided Sleeving, Expandable, 1.25" Dia, PA66 Monofilament, Black, 50 ft/reel

<b>Article Number</b>	170-03030
<b>Type</b>	BSPA661140
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• Nylon monofilament construction weave offers a tight, 12 mil braid that provides full coverage but will not rot or retain moisture.</li><li>• Material performs well in wet applications and where abiding substrate has a smooth surface.</li></ul>
<b>Quantity Per</b>	reel
<b>Product Description</b>	A pliable yet durable nylon sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.
<b>Short Description</b>	Braided Sleeving, Expandable, 1.25" Dia, PA66 Monofilament, Black, 50 ft/reel
<b>Global Part Name</b>	BSPA661140-PA66-BK

<b>Length L (Imperial)</b>	50.0
<b>Length L (Metric)</b>	15.2
<b>Bundle Diameter Min (Imperial)</b>	0.75
<b>Bundle Diameter Min (Metric)</b>	19.1
<b>Bundle Diameter Max (Imperial)</b>	1.5
<b>Bundle Diameter Max (Metric)</b>	38.1
<b>Diameter D (imperial)</b>	1.25
<b>Diameter D (metric)</b>	31.8
<b>Nominal Diameter (Imperial)</b>	1-1/4
<b>Nominal Diameter (Metric)</b>	31.8
<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	Non-Flammable
<b>Halogen free</b>	Yes
<b>Operating Temperature (Metric)</b>	-49°F to +302°F (-45°C to +150°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>UL Recognized (US)</b>	Yes
<b>UL Recognized (US and Canada)</b>	Yes
<b>Package Quantity(Imperial)</b>	50
<b>Package Quantity (Metric)</b>	15.24
<b>Customs Number</b>	3926909987
<b>Weight (Metric)</b>	0.40
<b>Weight (Imperial)</b>	0.89