

Stacked Coin Type

Not recommended for new design

Series : RF



Features

- Endurance : +85 °C 2000 h
- Can be discharged mA current
- RoHS compliant

Recommended applications

- Backup of data/RTC of base station, electronic meter, and industrial equipment
- For assist of rapid load change

Specifications

Category temp. range	-25 °C to +85 °C	
Maximum operating voltage	5.5 V.DC	
Nominal capacitance	0.1 F	0.68 F, 1.0 F
Characteristics at low temperature	Capacitance change	±30 % of initial measured value at +20 °C (at -25 °C)
	Internal resistance	≤ 5 times of initial measured value at +20 °C (at -25 °C)
Endurance	After 2000 hours application of maximum operating voltage at +85 °C	
	Capacitance change	±30 % of initial measured value at 20 °C
Shelf life	After 2000 hours storage at +85 °C without load (voltage)	
	Capacitance change	Capacitance change shall meet the specified limits for Endurance
	Internal resistance	Internal resistance shall meet the specified limits for Endurance

Dimensions in mm(not to scale)

Cap (F)	φD (mm)
0.1	13.5 max
0.68, 1.0	21.5 max

(Unit : mm)

Characteristics list

Maximum operating voltage (V.DC)	Capacitance (F)	Capacitance tolerance (F)	Internal resistance (Initial specified value) (Ω) at 1 kHz	Recommended discharge current (mA)	Parts number	Mass (Reference value) (g)	Min. packaging q'ty (pcs)
5.5	0.1	0.080 to 0.180	≤ 75	3 or less	EECRF0H104	3.3	200
	0.68	0.544 to 1.224	≤ 20	20 or less	EECRF0H684	10.0	100
	1.0	0.8 to 1.8	≤ 20	20 or less	EECRF0H105	10.0	100

Do not use reflow soldering. (IR, Atmospherheating methods, etc.) Please refer to the page of "Application guidelines".
The recommended discharge current is a reference value. Please design your equipment(circuit) in consideration of IR drop.